

FOREST RIVER INC.

CAMPING TRAILERS MAINTENANCE OF LIFTER SYSTEM

IN OUR OWNER'S MANUAL SECTION NUMBER FOUR, WE HAVE OUTLINED SEVERAL IMPORTANT STEPS THAT NEED TO BE TAKEN AND THAT YOU NEED TO KNOW ABOUT OUR ROOF LIFTER SYSTEM. IT IS VERY IMPORTANT TO LUBRICATE THE COMPLETE LIFTER SYSTEM AT LEAST ANNUALLY, OR FOLLOWING PROLONGED STORAGE. LUBRICATE AS FOLLOWS:

1. LIFTER POSTES – COAT WITH A LIQUID OR SPRAY TYPE SILICONE, OR LSD – 1 LUBRICANT.
2. SPROCKET GEARS – LUBRICATE WITH A THIRTY (30) WEIGHT OIL.
3. CHAINS AND PUSHER SPRINGS – LUBRICATE WITH A (30) WEIGHT OIL, OR WITH WD-40 SPRAY OIL.
4. CLUTCH SHAFT NUT – LUBRICATE WITH HEAVY GREASE, OR WITH A QUALITY MOTORCYCLE CHAIN LUBRICATION.
5. CLUTCH HEAD ASSEMBLY – LUBRICATE WITH (30) WEIGHT OIL, OR WITH A QUALITY MOTORCYCLE CHAIN LUBRICATION.

IT IS VERY IMPORTANT TO DO THESE STEPS TO PREVENT MOISTURE FROM ENTERING THE CAMPER AND CAUSING RUST. THIS IS ESPECIALLY TRUE FOR CAMPERS THAT ARE STORED OUTSIDE IN THE WINTER.

IT IS VERY IMPORTANT TO PERFORM THESE PRECAUTIONS TO PREVENT EXCESSIVE AND UNNECESSARY WEAR OF THE INTERNAL WORKING PARTS OF THE ROOF LIFTER SYSTEM, AND TO ENSURE LONG LIFE OF THESE INTERNAL PARTS.

FAILURE TO PERFORM THE ABOVE GENERAL CARE AND MAINTENANCE STEPS, AND FAILURE TO PROVIDE A GENERAL CARE AND MAINTENANCE RECORD, WHEN REQUESTED, CAN VOID OUR LIMITED LIFE-TIME WARRANTY OF THE ROOF LIFTER – SYSTEM, TO THE ORIGINAL OWNER.

BE SURE TO ADVISE THE OWNER THAT THESE MAINTENANCE AND CARE PROCEDURES ARE NECESSARY TO ENSURE LONG LIFE AND LONG USAGE, AND TO KEEP THE LIMITED WARRANTY VALIDATED.