



ADCO RV Cover Installation Guide



1. Ensure that you have purchased the correct size cover for your RV. Visit ADCOprod.com to review sizing. Make sure to measure your RV from end to end including bumpers, spare tire and ladder, but excluding the hitch (where applicable) and mirrors that extend beyond the front of the coach. If you have any doubts, call ADCO at (800) 541-2326 or call HannaRV.com customer service at (414) 762-7950 to speak with a product representative.
2. Clean your RV thoroughly. Otherwise, you run the risk of black streaks. On <http://www.hannarv.com/> you will find a large selection of RV cleaning products for you to use.
3. Pad all sharp edges on the RV, to include rain gutters (use the included rain gutter covers), steps, ladders (use the included ladder cap), and abrasive corners. The cover may shift in the wind and could tear if sharp edges are not properly padded. ADCO does not warrant this product against wind damage. You will want to cover the ladder cap last so that it's usable during installation.

NOTE: Installation does not require you to climb on the roof. A step ladder may be used. It is however much faster to install if you are able to safely walk on your RV's roof.

4. Unroll the RV Cover adjacent to your RV. Unwind the straps and buckles.
5. Turn the cover inside out while it's on the ground.
6. Roll it back up loosely so that the FRONT tag is the last part that is not rolled up.
7. Grab the FRONT tag in your hand and climb the ladder.
8. Turn around from the roof and pull the cover up onto the roof (like you are pulling up a fire hose).
9. Walk the cover to the FRONT of the RV with the FRONT tag still in hand. Toss the FRONT of the cover towards the ground.
10. Begin spreading out the cover. If it was properly turned inside out, the sides should almost fall into place.
11. Ensure that the sides fall most of the way to the ground – far enough to where you can grab them once you are standing on the ground.

12. Begin your descent down the ladder, installing the ladder cap on your way. Then pull down the cover over the back of the coach.
 13. Before any bottom corners are secured, straighten out the cover on the coach so that it's centered properly. Only then should you secure the bottom corners. Once they are in place, **do not make further adjustments or pull the fabric or you risk tearing the cover.**
 14. Adjust the straps and buckles located at each end of the RV Cover. Doing so will secure any excess fabric and prevent shifting in light wind.
 15. Finally, secure the bottom straps and buckles. Use the weighted tie down buckles to help toss the straps beneath the coach. Cover straps should be moderately tight. **DO NOT OVERTIGHTEN.** No additional straps, buckles or rope should be used or you risk damaging your rubber roof or causing abrasion to the RV's finish.
 16. When you become a pro at covering your RV, it should take you no more than 15 minutes
22. Starting from the rear of the RV, roll the cover up so that the FRONT tag is left exposed at the end of the roll. Toss the rolled cover to the ground. The next time that you use it, it should be all ready to repeat the process.

Taking the Cover Off Your RV...

17. Disconnect the straps and buckles from the bottom, front and back of the RV.
18. Pull the cover off the front and rear corners.
19. Climb up the ladder while pulling the cover as you go.
20. Carefully walk to the front of the RV, avoiding A/C units and any portion of the cover that's not flat on the roof. Pull the front of the cover up onto the roof.
21. Now pull the sides up onto the roof, turning them inside out and forming a strip of cover that spans the length of the roof.