E-100

RV BUMPER HITCH

2

6/12/2007

GROSS LOAD CAPACITY WHEN USED AS A WEIGHT CARRYING HITCH: 3,500 LBS. TRAILER WEIGHT & 500 LBS. TONGUE WEIGHT. ***DO NOT EXCEED VEHICLE MANUFACTURER'S RECOMMENDED TOWING CAPACITY.***

Parts List					
ITEM	QTY	PART NUMBER	DESCRIPTION		
1	1	CM-E-100-WA	WELDMENT ASSEMBLY		
2	2	1/2-13 x 5/12 LG.	CARRIAGE BOLT		
3	2	1/2 - 13	HEX FLANGE NUT		

3

HITCH WEIGHT: <u>8</u> LBS.					
INSTALL TIME: <u>10</u> MINUTES					
INSTALL NOTES:					

INSTALLATION STEPS

1) LOCATE AND MARK CENTER OF VEHICLE BUMPER BEAM.

2) POSTION HITCH OVER BUMPER BEAM ON CENTER MARK. SECURE WITH 1/2-13" CARRIAGE BOLTS AND FLANGE NUTS.

3) TORQUE ALL 1/2" FASTENERS TO 75 LB-FT.

PERIODICALLY CHECK THIS RECEIVER HITCH TO ENSURE THAT ALL FASTENERS ARE TIGHT AND THAT ALL STRUCTURAL COMPONENTS ARE SOUND.

Curt Manufacturing Inc., warrants this product to be free of defects in material and/or workmanship at the time of retail purchase by the original purchaser. If the product is found to be defective, Curt Manufacturing Inc., may repair or replace the product, at their option, when the product is returned, prepaid, with proof of purchase. Alteration to, misuse of, or improper installation of this product voids the warranty. Curt Manufacturing Inc.'s liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for incidental or consequential loss or damage.

BUMPER BEAM