

HYDRO LIFE

THE BACTERIA FIGHTER • THE BACTERIA FIGHTER • THE BACTERIA FIGHTER

MODEL C-2471

NEW CARTRIDGE INSTALLATION OR REPLACEMENT:

Cartridge Replacement:

- 1.** Shut off water supply. Open faucet to relieve pressure, or if your filter has a red pressure release button, press it down.
- 2.** To remove filter housing unscrew housing from head assembly. (Caution: Housing is filled with water).
- 3.** Remove used cartridge.
- 4.** Carefully remove O'Ring from groove in housing. (Set it aside, don't lose it).
- 5.** To clean housing use soap and water, then rinse thoroughly.
- 6.** Carefully wipe O'Ring and coat with a solid lubricant such as petroleum jelly. (Vaseline) Place O'Ring in groove inside housing. Be sure it is properly seated to prevent leakage.
- 7.** Remove plastic wrap and insert cartridge into housing. The small end must face up (on C 2063). Screw housing to filter cap. Hand tighten only, do not use wrench.

Important:

- Replace filter annually to maintain highest water quality, however, if flow is reduced because of sediment, or an undesirable taste or odor appears, replace filter immediately with Hydro Life cartridge Model C 2063, C 2471.
- To winterize, remove cartridge from housing, reconnect empty housing and winterize. After winterizing, clean housing and reinsert cartridge. Do not allow winterizing fluid to pass through the cartridge.
- If your RV or Watercraft is not regularly used, open a faucet and allow water to flow for a minute, to flush the system.
- To help maintain a quality water supply, it is recommended the fresh water tank be chlorinated regularly.
- Do not allow filter to freeze.
- Do not use with water that is microbiologically unsafe or unknown quality without adequate disinfection before or after the system.



Made in USA

Hydro Life, Inc. • 503 Maple St. • Bristol, IN 46507 • 1-800-626-7130 • 1-574-848-7700 • Fax 1-574-848-1400 • e-mail hydrolif@npcc.net